

Pressure-Temperature Guide – ENG

Saturated Conditions – Pressure (psig)

Temp. °F	Freon® 22 R-22	Suva® 123 R-123	Suva® 134a R-134a	Suva® 404A R-404A	Suva® 410A R-410A	Suva® 507 R-507	Temp °C
-40	0.6	28.9"	14.8"	4.9	10.8	5.4	-40
-38	1.4	28.8"	13.9"	5.9	12.1	6.4	-39
-36	2.2	28.7"	12.9"	7.0	13.4	7.5	-38
-34	3.1	28.6"	12.0"	8.0	14.8	8.6	-37
-32	4.0	28.5"	10.9"	9.2	16.3	9.8	-36
-30	4.9	28.4"	9.8"	10.3	17.8	11.0	-34
-28	5.9	28.3"	8.7"	11.5	19.4	12.2	-33
-26	6.9	28.2"	7.5"	12.8	21.0	13.5	-32
-24	8.0	28.1"	6.3"	14.1	22.7	14.8	-31
-22	9.1	27.9"	5.0"	15.4	24.5	16.2	-30
-20	10.2	27.8"	3.7"	16.8	26.3	17.6	-29
-18	11.4	27.6"	2.3"	18.3	28.2	19.1	-28
-16	12.6	27.5"	0.8"	19.8	30.2	20.6	-27
-14	13.9	27.3"	0.3	21.3	32.2	22.2	-26
-12	15.2	27.2"	1.1	22.9	34.3	23.8	-24
-10	16.5	27.0"	1.9	24.6	36.5	25.5	-23
-8	17.9	26.8"	2.8	26.3	38.7	27.3	-22
-6	19.4	26.6"	3.6	28.0	41.0	29.1	-21
-4	20.9	26.4"	4.6	29.8	43.4	30.9	-20
-2	22.4	26.2"	5.5	31.7	45.9	32.8	-19
0	24.0	25.9"	6.5	33.7	48.4	34.8	-18
2	25.7	25.7"	7.5	35.7	51.1	36.9	-17
4	27.4	25.4"	8.5	37.7	53.8	39.0	-16
6	29.1	25.2"	9.6	39.8	56.6	41.1	-14
8	31.0	24.9"	10.8	42.0	59.5	43.4	-13
10	32.8	24.6"	11.9	44.3	62.4	45.7	-12
12	34.8	24.3"	13.1	46.6	65.5	48.1	-11
14	36.8	23.9"	14.4	49.0	68.6	50.5	-10
16	38.8	23.6"	15.7	51.5	71.9	53.0	-9
18	40.9	23.2"	17.0	54.0	75.2	55.6	-8
20	43.1	22.9"	18.4	56.6	78.7	58.3	-7
22	45.3	22.5"	19.9	59.3	82.2	61.0	-6
24	47.6	22.1"	21.3	62.0	85.8	63.8	-4
26	50.0	21.7"	22.9	64.8	89.6	66.7	-3
28	52.4	21.2"	24.5	67.7	93.4	69.7	-2
30	55.0	20.8"	26.1	70.7	97.4	72.7	-1
32	57.5	20.3"	27.8	73.8	101.4	75.9	0
34	60.2	19.8"	29.5	76.9	105.6	79.1	1
36	62.9	19.3"	31.3	80.2	109.9	82.4	2
38	65.7	18.7"	33.1	83.5	114.3	85.8	3
40	68.6	18.2"	35.0	86.9	118.8	89.2	4
42	71.5	17.6"	37.0	90.4	123.4	92.8	6
44	74.5	17.0"	39.0	94.0	128.2	96.5	7
46	77.6	16.3"	41.1	97.6	133.0	100.2	8
48	80.8	15.7"	43.2	101.4	138.0	104.1	9
50	84.1	15.0"	45.4	105.3	143.2	108.0	10
52	87.4	14.3"	47.7	109.2	148.4	112.0	11
54	90.8	13.5"	50.0	113.3	153.8	116.2	12
56	94.4	12.8"	52.4	117.4	159.3	120.4	13
58	98.0	12.0"	54.9	121.7	164.9	124.7	14

"Denotes inches of mercury ("Hg)

Saturated Conditions – Pressure (psig)

Temp. °F	Freon® 22 R-22	Suva® 123 R-123	Suva® 134a R-134a	Suva® 404A R-404A	Suva® 410A R-410A	Suva® 507 R-507	Temp °C
60	101.6	11.2"	57.4	126.0	170.7	129.2	16
62	105.4	10.3"	60.0	130.5	176.6	133.7	17
64	109.3	9.4"	62.7	135.0	182.7	138.4	18
66	113.2	8.5"	65.4	139.7	188.9	143.1	19
68	117.3	7.6"	68.2	144.4	195.3	148.0	20
70	121.4	6.6"	71.1	149.3	201.8	153.0	21
72	125.7	5.6"	74.1	154.3	208.4	158.1	22
74	130.0	4.6"	77.1	159.4	215.2	163.3	23
76	134.5	3.5"	80.2	164.6	222.2	168.6	24
78	139.0	2.4"	83.4	169.9	229.3	174.1	26
80	143.6	1.2"	86.7	175.4	236.5	179.6	27
82	148.4	0.0"	90.0	181.0	244.0	185.3	28
84	153.2	0.6	93.5	186.7	251.6	191.1	29
86	158.2	1.2	97.0	192.5	259.3	197.1	30
88	163.2	1.8	100.6	198.4	267.3	203.1	31
90	168.4	2.5	104.3	204.5	275.4	209.3	32
92	173.7	3.2	108.1	210.7	283.6	215.6	33
94	179.1	3.9	112.0	217.0	292.1	222.1	34
96	184.6	4.6	115.9	223.4	300.7	228.7	36
98	190.2	5.3	120.0	230.0	309.5	235.4	37
100	195.9	6.1	124.2	236.8	318.5	242.3	38
102	201.8	6.9	128.4	243.6	327.7	249.3	39
104	207.7	7.7	132.7	250.6	337.1	256.5	40
106	213.8	8.5	137.2	257.8	346.7	263.8	41
108	220.0	9.4	141.7	265.1	356.5	271.2	42
110	226.4	10.3	146.4	272.5	366.4	278.8	43
112	232.8	11.2	151.1	280.1	376.6	286.6	44
114	239.4	12.1	156.0	287.9	387.0	294.5	46
116	246.1	13.1	160.9	295.8	397.6	302.6	47
118	253.0	14.1	166.0	303.8	408.4	310.8	48
120	260.0	15.1	171.2	312.1	419.4	319.2	49
122	267.1	16.1	176.5	320.4	430.7	327.8	50
124	274.3	17.2	181.8	329.0	442.1	336.5	51
126	281.7	18.3	187.4	337.7	453.8	345.4	52
128	289.2	19.4	193.0	346.6	465.8	354.5	53
130	296.9	20.6	198.7	355.6	477.9	363.8	54
132	304.7	21.7	204.6	364.9	490.3	373.2	56
134	312.6	22.9	210.6	374.3	503.0	382.9	57
136	320.7	24.2	216.7	383.9	515.9	392.7	58
138	329.0	25.5	222.9	393.7	529.1	402.7	59
140	337.4	26.8	229.2	403.7	542.5	413.0	60
142	345.9	28.1	235.7	413.9	556.2	423.4	61
144	354.6	29.5	242.3	424.3	570.2	434.1	62
146	363.5	30.9	249.0	434.9	584.5	445.0	63
148	372.5	32.3	255.9	445.7	599.0	456.1	64
150	381.7	33.8	262.9	456.8	613.88	467.4	66

For Further Information: (800) 235-SUVA

www.suva.dupont.com

DuPont Fluorochemicals
Wilmington, DE 19880-0711

Copyright © 2005, DuPont or its affiliates. All rights reserved. The DuPont Oval Logo, DuPont™, The miracles of science™, The Science of Cool™, and Suva® are registered trademarks or trademarks of E. I. du Pont de Nemours and Company or its affiliates.



DuPont™ Suva®

REFRIGERANTS

Pressure-Temperature Guide – ENG

Superheat – Saturated Vapor Pressures

Typical PH Diagram
Superheat–Reference Point




Dew Point — Saturated Vapor (psig)

Temp. °F	Suva® MP39 R-401A	Suva® MP66 R-401B	Suva® HP80 R-402A	Suva® HP81 R-402B	Suva® 407C R-407C	Suva® 408A R-408A	Suva® 409A R-409A	Temp °C
-40	13.8"	12.4"	5.7	3.7"	4.6"	3.1	14.8"	-40
-38	12.9"	11.3"	6.8	4.7"	3.2"	4.0	13.9"	-39
-36	11.9"	10.3"	7.8	5.7"	1.6"	5.0	13.0"	-38
-34	10.9"	9.2"	9.0	6.7"	0.1"	5.9	12.0"	-37
-32	9.8"	8.0"	10.1	7.8"	0.8	7.0	10.9"	-36
-30	8.7"	6.8"	11.4	8.9"	1.6	8.0	9.9"	-34
-28	7.5"	5.5"	12.6	10.1	2.5	9.1	8.8"	-33
-26	6.2"	4.2"	13.9	11.3	3.4	10.3	7.6"	-32
-24	5.0"	2.8"	15.3	12.5	4.4	11.5	6.4"	-31
-22	3.6"	1.4"	16.7	13.8	5.4	12.7	5.1"	-30
-20	2.2"	0.1	18.2	15.1	6.5	14.0	3.8"	-29
-18	0.8"	0.8	19.7	16.5	7.5	15.3	2.4"	-28
-16	0.3	1.6	21.2	18.0	8.7	16.7	0.9"	-27
-14	1.1	2.4	22.9	19.4	9.9	18.1	0.3	-26
-12	1.9	3.3	24.5	21.0	11.1	19.6	1.0	-24
-10	2.8	4.2	26.3	22.6	12.3	21.1	1.8	-23
-8	3.6	5.1	28.0	24.2	13.7	22.7	2.7	-22
-6	4.5	6.1	29.9	25.9	15.0	24.3	3.5	-21
-4	5.4	7.1	31.8	27.7	16.4	26.0	4.4	-20
-2	6.4	8.1	33.8	29.5	17.9	27.7	5.3	-19
0	7.4	9.2	35.8	31.4	19.4	29.5	6.3	-18
2	8.5	10.3	37.9	33.3	21.0	31.3	7.3	-17
4	9.5	11.5	40.0	35.3	22.6	33.2	8.3	-16
6	10.7	12.7	42.3	37.3	24.3	35.2	9.4	-14
8	11.8	13.9	44.6	39.5	26.1	37.2	10.5	-13
10	13.0	15.2	46.9	41.6	27.9	39.3	11.6	-12
12	14.2	16.5	49.4	43.9	29.7	41.4	12.8	-11
14	15.5	17.9	51.9	46.2	31.7	43.6	14.0	-10
16	16.9	19.3	54.4	48.6	33.7	45.9	15.3	-9
18	18.2	20.8	57.1	51.1	35.7	48.2	16.6	-8
20	19.6	22.3	59.8	53.6	37.9	50.6	18.0	-7
22	21.1	23.8	62.6	56.2	40.1	53.1	19.4	-6
24	22.6	25.4	65.5	58.9	42.3	55.7	20.8	-4
26	24.2	27.1	68.5	61.6	44.7	58.3	22.3	-3
28	25.8	28.8	71.5	64.4	47.1	61.0	23.9	-2
30	27.4	30.6	74.7	67.3	49.6	63.7	25.5	-1
32	29.1	32.4	77.9	70.3	52.1	66.6	27.1	0
34	30.9	34.2	81.2	73.4	54.8	69.5	28.8	1
36	32.7	36.2	84.6	76.5	57.5	72.5	30.5	2
38	34.6	38.2	88.1	79.8	60.3	75.6	32.3	3
40	36.5	40.2	91.6	83.1	63.2	78.7	34.2	4
42	38.5	42.3	95.3	86.5	66.1	81.9	36.1	6
44	40.5	44.5	99.0	90.0	69.2	85.3	38.0	7
46	42.6	46.7	102.9	93.5	72.3	88.7	40.1	8
48	44.8	49.0	106.8	97.2	75.5	92.2	42.1	9
50	47.0	51.4	110.9	101.0	78.8	95.7	44.3	10

"Denotes inches of mercury ("Hg)

Subcooling – Saturated Liquid Pressures

Typical PH Diagram
Subcooling–Reference Point



Bubble Point — Saturated Liquid (psig)

Temp. °F	Suva® MP39 R-401A	Suva® MP66 R-401B	Suva® HP80 R-402A	Suva® HP81 R-402B	Suva® 407C R-407C	Suva® 408A R-408A	Suva® 409A R-409A	Temp °C
50.0	57.9	62.4	115.4	106.3	97.9	96.8	60.9	10
52.0	60.4	65.1	119.6	110.3	101.7	100.5	63.4	11
54.0	63.0	67.8	123.9	114.3	105.6	104.3	66.1	12
56.0	65.7	70.6	128.3	118.4	109.6	108.1	68.8	13
58.0	68.4	73.5	132.8	122.6	113.7	112.1	71.6	14
60.0	71.2	76.5	137.4	127.0	117.9	116.1	74.5	16
62.0	74.1	79.5	142.1	131.4	122.3	120.3	77.4	17
64.0	77.0	82.6	147.0	135.9	126.7	124.5	80.4	18
66.0	80.0	85.7	151.9	140.6	131.2	128.8	83.4	19
68.0	83.1	89.0	157.0	145.3	135.8	133.3	86.6	20
70.0	86.3	92.3	162.1	150.1	140.5	137.8	89.8	21
72.0	89.5	95.7	167.4	155.1	145.4	142.5	93.1	22
74.0	92.8	99.2	172.8	160.1	150.3	147.2	96.5	23
76.0	96.2	102.8	178.3	165.3	155.4	152.1	99.9	24
78.0	99.7	106.4	183.9	170.6	160.5	157.0	103.4	26
80.0	103.2	110.2	189.7	176.0	165.8	162.1	107.0	27
82.0	106.8	114.0	195.5	181.5	171.2	167.3	110.7	28
84.0	110.6	117.9	201.5	187.1	176.8	172.6	114.4	29
86.0	114.4	121.9	207.7	192.9	182.4	178.0	118.3	30
88.0	118.2	125.9	213.9	198.7	188.2	183.5	122.2	31
90.0	122.2	130.1	220.3	204.7	194.1	189.2	126.2	32
92.0	126.2	134.3	226.8	210.8	200.1	194.9	130.3	33
94.0	130.4	138.7	233.5	217.1	206.3	200.8	134.5	34
96.0	134.6	143.1	240.2	223.4	212.5	206.8	138.8	36
98.0	138.9	147.7	247.1	229.9	219.0	212.9	143.1	37
100.0	143.3	152.3	254.2	236.5	225.5	219.2	147.6	38
102.0	147.8	157.0	261.4	243.3	232.2	225.5	152.1	39
104.0	152.4	161.8	268.7	250.2	239.0	232.0	156.7	40
106.0	157.1	166.7	276.2	257.2	245.9	238.7	161.4	41
108.0	161.9	171.8	283.9	264.4	253.0	245.4	166.3	42
110.0	166.8	176.9	291.6	271.7	260.3	252.3	171.2	43
112.0	171.8	182.1	299.6	279.1	267.6	259.4	176.2	44
114.0	176.8	187.4	307.7	286.7	275.1	266.6	181.3	46
116.0	182.0	192.9	315.9	294.4	282.8	273.9	186.5	47
118.0	187.3	198.4	324.3	302.3	290.6	281.3	191.8	48
120.0	192.7	204.0	332.9	310.3	298.6	288.9	197.2	49
122.0	198.2	209.8	341.6	318.5	306.7	296.7	202.7	50
124.0	203.8	215.7	350.5	326.8	315.0	304.6	208.3	51
126.0	209.5	221.6	359.5	335.3	323.4	312.6	214.0	52
128.0	215.3	227.7	368.7	343.9	332.0	320.8	219.8	53
130.0	221.2	233.9	378.1	352.7	340.7	329.2	225.7	54
132.0	227.2	240.3	387.7	361.7	349.7	337.7	231.8	56
134.0	233.4	246.7	397.5	370.8	358.7	346.3	237.9	57
136.0	239.7	253.3	407.4	380.1	368.0	355.2	244.2	58
138.0	246.0	259.9	417.5	389.6	377.4	364.1	250.5	59
140.0	252.5	266.7	427.8	399.2	387.0	373.3	257.0	60
142.0	259.1	273.6	438.3	409.0	396.7	382.6	263.6	61
144.0	265.9	280.7	449.0	419.0	406.6	392.1	270.3	62
146.0	272.7	287.9	459.9	429.1	416.7	401.8	277.1	63
148.0	279.7	295.2	471.0	439.5	427.0	411.7	284.0	64
150.0	286.8	302.6	482.4	450.0	437.5	421.7	291.1	66