



REFRIGERATION TECHNOLOGIES



RT375A EXPANDING FOAM FOAMING AEROSOL COIL CLEANER & DEGREASER

- Replaces the toxic coil blasters
 - No hazardous vapors or toxic ingredients
- 17 oz.



RT390G HEAVY DUTY CONCENTRATE

- Biodegradable • Neutral pH
- Non-Irritating • No Odors
- Non-Toxic



cps® TR600 REFRIGERANT RECOVERY MACHINE

- Powerful 2/3 HP oil-less 2 cylinder reciprocating recovery compressor
- Fast recovery in high temperature environments
- Automatic low pressure shut-off feature turns unit off when recovery is completed
- R-410a ready with 550 Psi high pressure shut-off switch



LS2 cps® LEAK-SEEKER II featuring E_MOS technology

- Microprocessor controlled sensor electronics
- Software managed sensor rejuvenation mode
- Sensitivity remains constant over the life of the sensor
- Dynamic signal analysis and automatic sensitivity control

BTLE9 TUBING TOOL



cps® BLACK MAX®

- Premium Multi-Head Tube Expander w/Color Coded Heads For: 1/4", 5/16", 3/8", 1/2", 5/8", 3/4", 7/8", 1", 1-1/8"
- Includes 1/4" + 5/16" Expander Heads

SWH SUPPLY COMPANY
FAMILY OWNED & OPERATED | SINCE 1937
HVAC/R SUPPLY CENTER

With over 30,000 items in stock!

LOUISVILLE
242 East Main St.
Louisville, KY 40202
Ph 502 589-9287

JEFFERSONTOWN
11208 Bluegrass Pkwy.
Jeffersontown, KY 40299
Ph 502 261-9287

LEXINGTON
1290 Industry Rd.
Lexington, KY 40505
Ph 859 254-8273

CINCINNATI
5197 Fishwick Dr.
Cincinnati, OH 45216
Ph 513 641-4422

www.swhsupply.com

GREAT PRODUCTS
From Our March /April 2016
Featured Vendors:



Not All Products Available at All Locations



www.swhsupply.com





DS-20000S WIRELESS SCALE



- User defined weight and approaching alarms
- Email accessible data logging
- Adjustable unit of measure
- Water-resistant design
- Wireless Bluetooth 4.0 Connection
- Light or dark app theme for visibility in different environments with the free JB app
- 24 month warranty

DV-40S WIRELESS VACUUM GAUGE



- Accurately measures vacuum from 12,000 microns down to 10 microns
- Programmable alarms
- Wireless Bluetooth® 4.0 Connection
- Share data reports via email
- Free DV-40S App for Apple and Android Devices
- 12 month warranty

PLATINUM

DV-200N PLATINUM PUMP 7 CFM

- Gas Ballast and Isolation Valve
- Lift ring
- All metal construction including all brass fittings
- Vacuum rating: 15 micron vacuum
- 24 Month Limited OTC Warranty



Control. Program. Monitor. Relax Heatcraft Refrigeration Controls Portfolio

Heatcraft Worldwide Refrigeration offers a complete portfolio of Refrigeration Controls to enhance commercial refrigeration performance in Food Service and Cold Storage applications.



- **NEW Quick Response Controller** - Enjoy quick, easy installation with this factory installed control solution.
- **Remote Refrigeration Control** - Manage your refrigeration system with this internet-based control.
- **Lead Lag Temperature Controller** - Combines the functionality of a room thermostat with a staging controller to reduce control complexity.
- **Split System Controller** - This controller combines three mechanical components into one electronic solution to reduce defrost complexity.
- **Variable Speed EC Motor with Orbus Controller** - Provides quick response to load changes and stable head pressure dramatically reducing energy consumption.
- **Beacon II Refrigeration System** - Electronic-based control system that provides mounted components to reduce field installation time.

THE QUICKEST WAY TO COOL

Quick Response Controller



- Factory installed and tested controls solution
- Quick, easy installation and programming
- Automatic superheat adjustment and precise temperature control
- Intelligent defrost
- Fan cycling during compressor off-cycle

RELIABLE & EFFICIENT PROCESS COOLING SOLUTIONS Air-cooled Package Chillers

- Improved heat transfer
- Advanced Microprocessor Controllers optimize operation
- Enhanced refrigerant leak protection
- Single or dual compressor configurations
- Scroll or reciprocating compressors
- R407A & R407C models available



22985 60", 3-PACK, PLUS II 1/4" HOSE W/ SEALRIGHT™ FITTING

- Low loss anti-blow back SealRight™ fitting traps refrigerant in hose when disconnected helping meet non-venting regulations & preventing finger burns
- 45° End for easy installation in tight areas

42004 SERIES 41 MANIFOLD WITH 3-1/8" GAUGES



- Color-coded scales
- Sliding double "O" ring pistons reduce wear
- Long life nylon seats
- Forged brass body for durability
- Full porting maximizes capacity and flow
- Includes color-coded, 60" PLUS II™ hoses with standard 1/4" flare fittings
- Hose assemblies UL recognized for 4000 psi (275 bar) burst and 800 psi (55 bar) working pressure

93560 6 CFM SUPERVAC™ VACUUM PUMP



- Isolation valve for oil changes without losing vacuum in the system
- Built-in vacuum indicator gauge
- Wide-mount oil reservoir port for easier, cleaner filling

JUST BETTER!